



Cart may be fitted with up to three rows of tall drawers

#### True Ergonomics

- Ergonomic back-tilt keyboard tray with left or right mouse tray ensures wrists remain in a neutral position during data entry—avoid repetitive-stress injuries while increasing comfort and productivity
- Designed for users 5'0" to 6'1" (152 to 185 cm) tall and for prolonged sitting or standing applications. The exceptional height adjustment range means shorter and taller users can work comfortably and productively in a seated as well as standing position
- LCD height adjustment range of at least 25" (63.5 cm) is standard on all LCD carts
- Patented CF™ lift-and-pivot motion technology minimizes forces required to adjust cart position: Casters, height adjustment, LCD tilt and pan all require just a touch
- Arm adjusts screen down low to the worksurface for people wearing bifocals or using a tablet PC

#### Safe

- For patient and caregiver safety the entire power system and the FULL cart are certified to UL/EN/IEC 60601-1 and CAN/CSA-C22.2 No. 60601-1:08. Also complies with EMI limits of FCC Part 15 Class A
- Power System User Interface integrated conveniently on the worksurface (includes visual and audible battery status indicator)
- Surfaces are treated with antimicrobial for product protection; handles are smooth and continuous for improved cleanability
- Environmentally clean: RoHS, REACH, WEEE and EU (94/62/EC) packaging compliant
- Durable, easy-to-clean exterior composed of aluminum, high-grade plastic and zinc-plated steel promotes infection control
- Large, smooth worksurface; easy-to-clean design promotes infection control
- Lockable, ventilated enclosed storage for closed notebook, thin client or CPU. Keys and locks are heavy-duty
- Locking casters
- CPU lock provided inside the storage compartment for additional security
- Designed to meet guidelines established by the American National Standards Institute for computer use

#### Service

- Includes FREE StyleLink with enterprise capabilities: Install, access and manage your StyleView power systems from a remote location across WAN, LAN, or VPN
- Covered by Global Service Program—24/7 coverage

#### All the Details Covered

- Drawer dividers are included, allowing compartments to be customized to match your workflow requirements
- Four amber LEDs provide light over keyboard tray; includes 15-minute auto shut-off
- Button for LED lights is located conveniently on worksurface
- Rear basket keeps task-related items where they can be quickly accessed
- Universal mounting slot for accessories and equipment
- A unique cable management system conceals and organizes cords, making cleaning easy
- Ships fully assembled
- Quick, easy access to CPU storage compartment: One-hand operation of secure latch with slide-out worksurface ensures easy access. Security cable in compartment deters CPU theft
- Four-port USB hub
- Easy access to components for field replacement and serviceability: keyboard LEDs, PC boards (including the user interface). Easier, faster upkeep and service means less down time
- Pre-routed cables provide quicker integration with equipment
- Onboard power strip with three or two receptacles (country dependent)
- Four (4) ultra-smooth gliding casters for extremely easy push/pull mobility; locking casters ensure lock-in-place stability

#### Compatibility and Dimensions

- Internal Dimensions: medium drawer = 2.5"H x 5.5"W x 10.5"D (63.5 x 140 x 267 mm)—includes dividers to configure up to 4 compartments
- Open-architecture design accommodates multiple configurations, closed notebooks with monitor (even widescreen with up to 17.3" diagonal size), CPU and monitor, thin clients, tablets, all-in-one computers and future hardware upgrades
- Storage compartment for closed notebook, thin client or CPU: 17.75"W x 14.75"D x 4"H (45 x 37.5 x 10.1 cm); larger computers can mount to rear of cart with Universal CPU Holder accessory (ordered separately)
- Compact Wheel-to-Wheel Base Dimensions: 15.5" x 17" (394 x 432 mm)
- Worksurface Dimensions: 22.4"W x 19.75"D (567 x 502 mm)
- Mounting Standards: VESA FDMI MIS-D, 100/75, C (hole pattern: 100 x 100 mm & 75 x 75 mm)
- VAC:
  - SV44-12A1-1 = 120V/60Hz
  - SV44-12A1-2 = 230V/50Hz
  - SV44-12A1-3 = 230V/50Hz
  - SV44-12A1-6 = 100V/50Hz
  - SV44-12A1-7 = 220V/60Hz
  - SV44-12A1-8 = 220V/60Hz
  - SV44-12A1-C = 230V/50Hz
- Grounded Plug:
  - SV44-12A1-1 = NEMA 5-15P Hospital Grade
  - SV44-12A1-2 = European CEE 7
  - SV44-12A1-3 = UK BS 1363
  - SV44-12A1-6 = JIS 8303
  - SV44-12A1-7 = UK BS 1363
  - SV44-12A1-8 = European CEE 7
  - SV44-12A1-C = SEV 1011
- 66 Ah Power System with two (2) 33 Ah, 12 V DC, Sealed Lead Acid (SLA), Absorbed Glass Mat (AGM), valve-regulated batteries with supporting electronics

It is recommended that a discharge test be conducted when cart is first purchased to determine runtime with computer equipment configured on the cart. Change batteries when instructed by StyleLink battery management software. If StyleLink is not used, it is strongly recommended a monthly discharge test be conducted to determine runtime loss. If runtime is less than 50% of original, batteries must be changed

Shipping Dimensions: 24.5"W x 34"D x 56"H (62 x 87 x 142 cm)

Shipping Weight: 189 lbs (85.7 kg); actual cart weight = 155 lbs (70.3 kg)

Warranty: Five (5) years for cart's mechanical components, two (2) years on power module. See complete [warranty](#) for details

#### Support Material

<a href="#">StyleView Brochure</a>	English	pdf	4321 KB
<a href="#">Dimensional Illustrations</a>		pdf	3796 KB
<a href="#">Cleaning Instructions</a>	English	pdf	592 KB

<a href="#">Installation Manual</a>	English	pdf	6487 KB
<a href="#">Installation Manual</a>	English (for AU)	pdf	6467 KB
<a href="#">Quick Reference Guide</a>	English	pdf	442 KB
<a href="#">Instructional Video: User Guide</a>	English		KB

[Neem contact op](#) | [OmniMount TV Mounts](#) | [Anthro Tech Furniture](#) | [Sitemap](#) | [Gebruiksvoorwaarden en privacybeleid](#) | [Garantiebepalingen](#)  
Copyright 1996-2016 Ergotron, Inc. Alle rechten voorbehouden