

3 ft Coax High Resolution Monitor VGA Cable - HD15 M/M

StarTech ID: MXT101MMHQ3



The MXT101MMHQ3 3-foot High Resolution VGA Monitor Cable is designed to provide the highest video quality possible through VGA and is ideally suited for high resolution VGA applications of 1920x1200 and above.

This durably constructed coaxial VGA cable features two HD15 (male) connectors and eliminates the picture "ghosting" and fuzzy images that are inherent to non-coaxial cables, while providing superior EMI interference protection by using ferrite cores near the connector ends.

Toepassingen

- Ideal for high resolution monitors (1920x1200 and above)
- Connect any VGA display to a VGA source
- Connect a high resolution display to a Desktop PC or video switch, up to 3 feet away

Eigenschappen

- Triple-coaxial + twisted-pair wire for crystal clear display
- Impedance matched at 75 Ohms for full brightness and vibrant picture color
- Molded connector ends with strain relief
- Ferrite core eliminates EMI interference

Technische specificaties

| | |
|--------------------------|--|
| Warranty | Lifetime |
| Aantal geleiders | 14 |
| Connectormateriaal | Nikkel |
| Type kabelmantel | PVC - Polyvinyl Chloride |
| Kabelafscherming | Aluminum-Mylar folie met vlechtwerk |
| Brandbestendigheid | CMG goedgekeurd (algemeen doel) |
| Aantal ferrieten | 1 |
| Certificaties | UL2919 |
| Connector A | 1 - VGA (15 pin; High Density D-Sub) Male |
| Connector B | 1 - VGA (15 pin; High Density D-Sub) Male |
| Impedantie | 75 Ohm |
| Kleur | Zwart |
| Draaddikte | 28 AWG |
| Max. afmeting connector | 34 mm [1.3 in] |
| Kabellengte | 0.9 m [3 ft] |
| Buitendiameter kabel | 9 mm [0.4 in] |
| Lengte product | 0.9 m [3 ft] |
| Breedte product | 32 mm [1.3 in] |
| Hoogte product | 15 mm [0.6 in] |
| Gewicht product | 192 g [6.8 oz] |
| Bedrijfstemperatuur | 0 to 60 °C |
| Opslagtemperatuur | -20 to 80 °C |
| Vochtigheid | 0 - 80 %RH |
| Verzendgewicht (verpakt) | 200 g [7.1 oz] |
| Meegeleverd | 1 - 3 ft Coax High Resolution VGA Monitor Cable - HD15 M/M |
| Meegeleverd | 2 - Nuts |

Certificaties, rapporten en compatibiliteit

